Apart Audio

Net Price List PROFESSIONAL USER

ALL PRICES AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Pro-Sound & Lighting Solutions

www.pro-technica.com

BGN

Price List 3/2015

Effective March 6-th 2015

Subject to change without prior notice.
All former price lists expire with the publishing of this version.
All prices are suggested net retail prices; ex works.
There are applicable our General Terms of Business, only.

Aricles marked * will be discontinued soon!

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		LOUDSPEAKERS		
		100V CEILING SPEAKERS *PAINTCM (option: any RAL Colour)*		
	CM3T **CM3T-BL** **CM3T-SLV**	**3" Halogen-spot size** ceiling speaker, Rated Power: 10W 16Ohm, 1.5/3/6W 100V Freq. Response 120 Hz - 18 kHz, Sensitivity 87dB/1W/1m, Dimensions: Φ105x70mm, Mounting hole diameter: Φ82mm, IP54, white, black or silver	29,00	**34,80** BGN
	CM4	**4" ceiling speaker with backcan**, Rated Power: 15W 16Ohm, built in low cut filter Freq. Response 100 Hz - 20 kHz, Sensitivity 88dB/1W/1m, Dimensions: Φ135x100mm, Mounting hole diameter: Φ115mm, IP60, white	53,00	**63,60** BGN
	CM4T **CM4T-BL** **CM4T-SLV**	**4"** ceiling speaker, Rated Power: 15W 16Ohm, 1.5/3/6W 100V Freq. Response 90 Hz - 19 kHz, Sensitivity 88dB/1W/1m, Dimensions: Φ135x74mm, Mounting hole diameter: Φ105mm, IP50, white, black or silver	35,00	**42,00** BGN
	CM5EH	**5" Dual cone** ceiling speaker, Rated Power: 3/6W 100V , best buy for public tenders, Freq. Response 100 Hz - 18 kHz, Sensitivity 91dB/1W/1m, Dimensions: Φ178x53mm, Mounting hole diameter: Φ160mm, IP54, white	22,00	**26,40** BGN
	CM6E **CM6E-BL** **CM6E-SLV**	**6.5" Dual Cone** ceiling speaker, Rated Power: 6W 8Ohm, 1.5/3/6W 100V Freq. Response 70 Hz - 20 kHz, Sensitivity 93dB/1W/1m, Dimensions: Φ205x70mm, Mounting hole diameter: Φ183mm, IP50, white, black or silver	32,00	**38,40** BGN
	CM6QFT	**2-way low profile** ceiling speaker, **6,5" woofer 1" tweeter** Rated Power: 40W 16Ohm, 1.5/3/6W 100V Freq. Response 60 Hz - 20 kHz, Sensitivity 91dB/1W/1m, Dimensions: Φ237x65mm, Mounting hole diameter: Φ216mm, IP50, white	67,00	**80,40** BGN
NEW	**CM6TSMF**	**6.5"** ceiling speaker **metal frame, metal fire dome, thermal fuse, ceramic connector** Rated Power: 1.5/3/6W 100V, Freq. Response 70 Hz - 18 kHz, Sensitivity 93dB/1W/1m, Dimensions: Φ217x130mm, Mounting hole diameter: Φ205mm, IP60, white	67,00	**80,40** BGN
	CM6T	**2-way** ceiling speaker, **6,5" woofer 1" tweeter**, Rated Power: 40W 16Ohm, 1.5/3/6W 100V Freq. Response 60 Hz - 20 kHz, Sensitivity 92dB/1W/1m, Dimensions: Φ205x80mm, Mounting hole diameter: Φ183mm, IP54, white	58,00	**69,60** BGN
	CMBB	**Back-box (in-wall and on-wall)** for the APart CM6E - CM6T - CM20T and CM608 Dimensions: Φ230x80mm, white	26,00	**31,20** BGN
	CM20T **CM20T-BL** **CM20T-SLV**	**2-way** ceiling speaker, **6,5" woofer 1" tweeter**, Rated Power: 60W 16Ohm, 2.5/5/10/20W 100V Freq. Response 60 Hz - 20 kHz, Sensitivity 92dB/1W/1m, Dimensions: Φ205x80mm, Mounting hole diameter: Φ183mm, IP54, white, black or silver	70,00	**84,00** BGN
	CMX20T **CMX20T-BL**	**2-way** ceiling speaker, **8" woofer 1" tweeter**, Rated Power: 60W 16Ohm, 2.5/5/10/20W 100V Freq. Response 50 Hz - 20 kHz, Sensitivity 93dB/1W/1m, Dimensions: Φ244x90mm, Mounting hole diameter: Φ220mm, IP54, white or black	82,00	**98,40** BGN
		Low Impedance (8 Ohm) CEILING SPEAKERS *PAINTCM (option: any RAL Colour)*		
	CM608 **CM608-BL** **CM608-SLV**	**2-way** ceiling speaker, **6,5" woofer 1" tweeter**, Rated Power: 40W 8Ohm Freq. Response 60 Hz - 20 kHz, Sensitivity 93dB/1W/1m, Dimensions: Φ205x80mm, Mounting hole diameter: Φ183mm, IP54, white, black or silver	48,00	**57,60** BGN
	CM1008	**2-way** ceiling speaker, **8" woofer 1" tweeter**, Rated Power: 60W 8Ohm, Freq. Response 50 Hz - 20 kHz, Sensitivity 93dB/1W/1m, Dimensions: Φ244x90mm, Mounting hole diameter: Φ220mm, IP54, white	68,00	**81,60** BGN
	CMSUB8	**8" dual coil ceiling subwoofer**, Program Power 2x80watt, Rated Impedance 2x8Ohm Built in crossover, Freq. Response 50 Hz - 200 kHz, Sensitivity 88dB/1W/1m, Dimensions: Φ246x106mm, Mounting hole diameter: Φ226mm, IP54, white	144,00	**172,80** BGN
		MARINE & SAUNA SERIES		
	CMAR5-W	**2-way** build-in speaker for use in marine or very humid environments, **max. operating temperature 95°C** 5.25" woofer, 1" tweeter Rated Power 25W 8Ohm, Freq. Response 100 Hz - 20 kHz, Sensitivity 85dB/1W/1m, Dimensions: Φ152x55mm, Mounting hole diameter: Φ110mm, **IP65**, white	70,00	**84,00** BGN
	CMAR6-W	**2-way** build-in speaker for use in marine or very humid environments, **max. operating temperature 95°C** 6.5" woofer, 1" tweeter Rated Power 30W 8Ohm, Freq. Response 70 Hz - 20 kHz, Sensitivity 88dB/1W/1m, Dimensions: Φ190x61mm, Mounting hole diameter: Φ146mm, **IP65**, white	91,00	**109,20** BGN
	CMAR8-W	**2-way** build-in speaker for use in marine or very humid environments, **max. operating temperature 95°C** 8" woofer, 1" tweeter Rated Power 30W 8Ohm, Freq. Response 50 Hz - 20 kHz, Sensitivity 88dB/1W/1m, Dimensions: Φ221x76mm, Mounting hole diameter: Φ186mm, **IP65**, white	126,00	**151,20** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		DISTINCT IN-WALL SERIES *PAINTCM (option: any RAL Colour)*		
	CMS508	**Square 2-way HiFi loudspeaker; 5.25" woofer 1" tweeter**, Rated Power: 35W 8Ohm Freq. Response 60 Hz - 20 kHz, Sensitivity 90dB/1W/1m, Dimensions: 171x171x54mm, Cutout dimensions: 145x145mm, IP54, white	47,00	**56,40** BGN
	CMS15T	**Square 2-way HiFi loudspeaker; 5.25" woofer 1" tweeter** Rated Power: 35W 16Ohm, 2.5/5/10/15W 100 V Freq. Response 60 Hz - 20 kHz, Sensitivity 90dB/1W/1m, Dimensions: 171x171x61mm, Cutout dimensions: 145x145mm, IP54, white	63,00	**75,60** BGN
	CMS5BBI	**In-Wall metal backbox** with internal damping for CMS508/CMS15T/CMSQ108 Zincor treated metal for rust protection Outer box dimensions : 221 Wx221 Hx90 D (incl 9 mm rim) mm Outer rim dimensions : 148 Wx148 H mm	92,00	**110,40** BGN
	CMS608	**Square 2-way HiFi loudspeaker; 6.55" woofer 1" tweeter**, Rated Power: 40W 8Ohm Freq. Response 60 Hz - 20 kHz, Sensitivity 92dB/1W/1m, Dimensions: 201x201x75mm, Cutout dimensions: 176x176mm, IP54, white	54,00	**64,80** BGN
	CMS20T	**Square 2-way HiFi loudspeaker; 6.5" woofer 1" tweeter** Rated Power: 40W 16Ohm, 2.5/5/10/20W 100 V Freq. Response 60 Hz - 20 kHz, Sensitivity 92dB/1W/1m, Dimensions: 201x201x75mm, Cutout dimensions: 176x176mm, IP54, white	72,00	**86,40** BGN
	CMS6BBI	**In-Wall metal backbox** with internal damping for CMS608/CMS20 Zincor treated metal for rust protection Outer box dimensions : 251 Wx351 Hx90 D (incl 9 mm rim) mm Outer rim dimensions : 182 Wx182 H mm	100,00	**120,00** BGN
		DESIGN IN-WALL SERIES *PAINTCM (option: any RAL Colour)*		
	CMR608	**Rectangular 2-way HiFi loudspeaker; 5" woofer 1" tweeter**, Rated Power: 40W 8Ohm Freq. Response 60 Hz - 20 kHz, Sensitivity 92dB/1W/1m, Dimensions: 237x170x70mm, Cutout dimensions: 210x143mm, IP54, white	61,00	**73,20** BGN
	CMR20T	**Rectangular 2-way HiFi loudspeaker; 5.25" woofer 1" tweeter** Rated Power: 40W 16Ohm, 2.5/5/10/20W 100 V Freq. Response 60 Hz - 20 kHz, Sensitivity 92dB/1W/1m, Dimensions: 237x170x65mm, Cutout dimensions: 210x143mm, IP50, white	75,00	**90,00** BGN
	CMRBB	**Back-box** for on-wall mounting of the APart CMR types (CMR608 / CMR20T) High Quality ABS, Dimensions (HxWxD): 235x167x85 mm	23,00	**27,60** BGN
	CMRBBI	**In-Wall box** for CMR loudspeaker-range (CMR608 / CMR5 / CMR20T) Injected plastic, special grooves for optimal grip into concrete and cement Dimensions (HxWxD) : 214x150x85 mm	20,00	**24,00** BGN
		HI END IN-WALL SERIES		
	CMSQ108	**2-way** ceiling/in-wall high quality speaker 120W 8Ohm, 5,5" Dupont Kevlar woofer, 1" pivotable silk dome tweeter, ultra low profile edges, Freq. Response: 50 Hz - 25 kHz, Sensitivity 87dB/1W/1m, Dimensions: 167x167x80mm, Cutout dimensions: 145x145x73mm, white	128,00	**153,60** BGN
	CMRQ108	**2-way** ceiling/in-wall high quality speaker 120W 8Ohm, 6,5" Dupont Kevlar woofer, 1" pivotable silk dome tweeter, ultra low profile edges, Freq. Response 45 Hz - 25 kHz, Sensitivity 87dB/1W/1m, Dimensions: 296x198mm, Cutout dimensions: 272x172x78mm, white	175,00	**210,00** BGN
	CMRQ108BBI	**in-wall metal backbox** with internal damping for CMRQ108 Zincor treated metal for rust protection Outer box dimensions : 251 Wx351 Hx90 D (incl 9 mm rim) mm Outer rim dimensions : 179 Wx279 H mm	100,00	**120,00** BGN
	CMRQ108C	**2-way** ceiling/in-wall high quality speaker 100W 8Ohm, 2x5.3" Dupont Kevlar woofers, 1" pivotable silk dome tweeter, ultra low profile edges, Freq. Response 55 Hz - 25 kHz, Sensitivity 88dB/1W/1m, Dimensions: 346x176mm, Cutout dimensions: 323x153x69mm, white	209,00	**250,80** BGN
	CMRQ108CBBI	**in-wall metal backbox** with internal damping for CMRQ108C Zincor treated metal for rust protection Outer box dimensions : 402 Wx221 Hx90 D (incl 9 mm rim) mm Outer rim dimensions : 328 Wx158 H mm	100,00	**120,00** BGN
		FUNCTIONAL CABINET SERIES		
	SM6-G **SM6-W**	**On wall 5"** speaker, 1.5/3/6W 100V Frequency Response: 200Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions: 202x142x72mm; Weight 0,8kg; IP50; grey or white	30,00	**36,00** BGN
	SM6V-G **SM6V-W**	**On wall 5"** speaker with built-in volume control, 1.5/3/6W 100V Frequency Response: 200Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions: 202x142x72mm; Weight 0,8kg; IP50; grey or white	65,00	**78,00** BGN
	SM6VP-G **SM6VP-W**	**On wall 5"** speaker with built-in volume control and 24V priority relay 1.5/3/6W 100V, Frequency Response: 200Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions: 202x142x72mm; Weight 0,8kg; IP50; grey or white	80,00	**96,00** BGN
	SMB6-G **SMB6-W**	**On wall 5"** speaker with back plate and U-bracket 1.5/3/6W 100V, Frequency Response: 200Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions: 202x142x72mm; Weight 0,8kg; IP50; grey or white	40,00	**48,00** BGN
	SMB6V-G **SMB6V-W**	**On wall 5"** speaker with back plate and U-bracket, built-in volume control 1.5/3/6W 100V, Frequency Response: 200Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions: 202x142x72mm; Weight 0,8kg; IP50; grey or white	74,00	**88,80** BGN
	SMB6VP-G **SMB6VP-W**	**On wall 5"** speaker with back plate and U-bracket, built-in volume control and 24V priority relay 1.5/3/6W 100V, Frequency Response: 200Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions: 202x142x72mm; Weight 0,8kg; IP50; grey or white	89,00	**106,80** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		SOUND COLUMNS SERIES		
	COLS41	Extra slim column speaker for sound reproduction in acoustically difficult venues. **4x2" slim sound column speaker with 1" tweeter** 100V/20-10-5 W; 8Ohm/20W; Lo-cut filter; SPL 1W/1M: 95 dB; Frequency range : 250 Hz – 20 kHz; Dispersion at 1 kHz - Hor/Ver: 165°/ 75° IP rating : 66; Dimensions HxWxD (mm) : 400x66x66; Weight (kg) : 2.0, white	130,00	**156,00** BGN
	COLS81	Extra slim column speaker for sound reproduction in acoustically difficult venues. **8x2" slim sound column speaker with 1" tweeter** 100V/30-15-6 W; 16Ohm/30W; Lo-cut filter; SPL 1W/1M: 96 dB; Frequency range : 220 Hz – 20 kHz; Dispersion at 1 kHz - Hor/Ver: 165°/ 55° IP rating : 66; Dimensions HxWxD (mm) : 613x66x66; Weight (kg) : 2.9, white	235,00	**282,00** BGN
	COLS101	Extra slim column speaker for sound reproduction in acoustically difficult venues. **10x2" slim sound column speaker with 1" tweeter** 100V/40-20-10 W; 8Ohm/40W; Lo-cut filter; SPL 1W/1M: 97 dB; Frequency range : 200 Hz – 20 kHz; Dispersion at 1 kHz - Hor/Ver: 165°/ 50° IP rating : 66; Dimensions HxWxD (mm) : 723x66x66; Weight (kg) : 3.3, white	277,00	**332,40** BGN
	COLSBRA	Bracket for easy tilting and rotating of COLS sound columns Dimensions : 82x36x93 mm (LxWxH); Color : white; Net weight : 100 gram	26,00	**31,20** BGN
	COLW41	Elegant design column speaker, excellent audio directivity for music as well as speech **4x3.3" sound column speaker with 1" tweeter** 100V/40-30-15W 16Ohm/40W; Lo-cut filter; SPL 1W/1M: 97 dB; Frequency range : 190 Hz – 20 kHz; Dispersion at 1 kHz - Hor/Ver: 165°/ 65° IP rating : 66; Dimensions HxWxD (mm) : 555x100x83; Weight (kg) : 3.9, white	259,00	**310,80** BGN
	COLW81	Elegant design column speaker, excellent audio directivity for music as well as speech **8x3.3" sound column speaker with 1" tweeter**, 100V/80-40-30W 8Ohm/80W; Lo-cut filter; SPL 1W/1M: 98 dB; Frequency range : 170 Hz – 20 kHz; Dispersion at 1 kHz - Hor/Ver: 165°/ 45° IP rating : 66; Dimensions HxWxD (mm) : 974x100x83; Weight (kg) : 6.7, white	421,00	**505,20** BGN
	COLW101	Elegant design column speaker, excellent audio directivity for music as well as speech **10x3.3" sound column speaker with 1" tweeter** 100V/100-60-40W 8Ohm/100W; Lo-cut filter; SPL 1W/1M: 99 dB; Frequency range : 160 Hz – 20 kHz; Dispersion at 1 kHz - Hor/Ver: 165°/ 40° IP rating : 66; Dimensions HxWxD (mm) : 1180x100x83; Weight (kg) : 7.7	498,00	**597,60** BGN
	COLWBRA	Bracket for easy tilting and rotating of COLW sound columns Dimensions : 82x36x93 mm (LxWxH); Color : white; Net weight : 100 gram	26,00	**31,20** BGN
		SPECIAL SPEAKERS		
	ROCK608	Outdoor loudspeaker, "rock" design, 40W 8Ohm **6,5" woofer 1" tweeter**, Frequency Response: 60Hz-20kHz, Sensitivity: 93dB/1W/1m, Dimensions (HxWxD): 260x200x280mm, Weight: 7.2kg; IP64	158,00	**189,60** BGN
	ROCK20	Outdoor loudspeaker, "rock" design, 40W 8Ohm, 2.5/5/10/20W 100V **6,5" woofer 1" tweeter**, Frequency Response: 60Hz-20kHz, Sensitivity: 92dB/1W/1m, Dimensions (HxWxD): 260x200x280mm, Weight: 7.8kg; IP64	175,00	**210,00** BGN
	SPH16	2-way pendant sphere speaker,16W 8Ohm, 4/8/16W 100V **5.25" woofer 1" tweeter**, Frequency Response: 80Hz-20kHz, Sensitivity: 92dB/1W/1m, Dimensions (diameter): 180mm, 3m cable; Weight: 1.7kg; IP53	88,00	**105,60** BGN
	SPH20	**8" Dual Cone Pendant sphere** loudspeaker with 360° dispersion cone, 20W 8Ohm, 5/10/20W 100V Frequency Response: 80Hz-18kHz, Sensitivity: 99dB/1W/1m, Dimensions (diameter): 254mm, 3m cable; Weight: 2.3kg; IP63	103,00	**123,60** BGN
		OUTDOOR PAGING SERIES		
	H10-G	**Compact compression horn** loudspeaker, 10W 8Ohm, 1.25/2.5/5/10W 100V Frequency Response: 400Hz-10kHz, Sensitivity: 101dB/1W/1m, Dimensions: Φ140x192mm, Weight: 1.05kg, IP66, grey color	60,00	**72,00** BGN
	H20-G	**Powerful compression horn** loudspeaker, 20W 8Ohm, 2.5/5/10/20W 100V Frequency Response: 280Hz-9.5kHz, Sensitivity: 105dB/1W/1m, Dimensions: Φ200x232mm, Weight: 1.36kg, IP66, grey color	74,00	**88,80** BGN
	H30LT-G	**Long throw compression horn** loudspeaker, 30W 8Ohm, 5/10/15/30W 100V Frequency Response: 350Hz-9kHz, Sensitivity: 110dB/1W/1m, Dimensions (HxWxL): 258x212x288mm, Weight: 1.7kg, IP66, grey color	100,00	**120,00** BGN
	HM25-G	**Long throw compression aluminium horn** loudspeaker, 10/20/25W 100V Frequency Response: 300Hz-10kHz, Sensitivity: 103dB/1W/1m, Dimensions (DxL): 264x210mm, Weight: 1.9kg, IP66, grey color RAL7035	130,00	**156,00** BGN
	MPLT32-G	**High Quality 2-way long throw music projector** with 6,5" woofer + 1" horn driver, Aluminim bracket 4/8/16/32W 100V, Frequency Response: 75Hz-18kHz, Sensitivity: 106dB/1W/1m, Dimensions (HxWxL): 250x360x290mm, Weight: 4.9kg, IP66, grey color	298,00	**357,60** BGN
	MPLT62-G	**Very High Power 2-way long throw music projector** with 6,5" woofer + 1" horn driver, Aluminim bracket 8/16/32/64W 100V, Frequency Response: 75Hz-18kHz, Sensitivity: 106dB/1W/1m, Dimensions (HxWxL): 250x360x290mm, Weight: 5kg, IP66, grey color	343,00	**411,60** BGN
		OUTDOOR MUSIC SERIES		
	MP16-G	**Compact sound projector**, 5,5" coated woofer, all metal parts in aluminum or stainless steel 5/10/16W 100V; Frequency Response: 100Hz-18kHz, Sensitivity: 95dB/1W/1m, Dimensions: Φ138x200mm, Weight: 1.35kg, IP56, grey color	74,00	**88,80** BGN
	MP26-G	**Powerful sound projector**, 6,5" coated woofer, all metal parts in aluminum or stainless steel 10/20/26W 100V; Frequency Response: 90Hz-19kHz, Sensitivity: 96dB/1W/1m, Dimensions: Φ170x240mm, Weight: 1.75kg, IP56, grey color	95,00	**114,00** BGN
	MPBD20-G	**Bidirectional and angled sound projector**, 2x5" full range woofer, all metal parts in aluminum or stainless steel 5/10/20W 100V; Frequency Response: 150Hz-20kHz, Sensitivity: 93dB/1W/1m, Dimensions, incl. bracket: 270x142x165mm, Weight: 1.83kg, IP56, grey color	131,00	**157,20** BGN
	MPH31-G	**Horn loaded sound projector**, 5,25" woofer, 4/7.5/15/30W 100V; Frequency Response: 120Hz-15kHz, Sensitivity: 92dB/1W/1m, Dimensions: Φ180x215mm, Weight: 1.72kg, IP54, grey color	103,00	**123,60** BGN
		SDQ CABINET SERIES		
	SDQ5P-BL **SDQ5P-W**	Stereo 2-way loudspeakers set 1 active & 1 passive. 2x30W; **5.25" woofer, 1" tweeter**, black or white, Inputs: stereo RCA, stereo mini-jack, balanced stereo euroblock; Bass & Treble Tone Controls, THD: <0.07%; S/N Ratio: >90dB; SPL 1W/1m: 91dB Freq.Range: 45Hz-20 kHz; IP40; Dimensions without brackets (WxHxD): 182x252x170mm; Weight: 5.75 Kg, brackets included	230,00	**276,00** BGN
	SDQ5PIR-BL **SDQ5PIR-W**	Stereo 2-way loudspeakers set with IR & RS232 remote control. **1 active & 1 passive. 2x30W; 5.25" woofer, 1" tweeter**, black or white, Inputs: stereo mini-jack & balanced stereo euroblock; Auto-power-on; Bass & Treble Tone Controls, THD: <0.07%; S/N Ratio: >90dB; SPL 1W/1m: 91dB Freq.Range: 45Hz-20 kHz; IP40; IR remote & wall brackets included Dimensions (WxHxD): 182x252x170mm; Weight: 4.6 kg, black Optional wired remote control panels (ACP/ACPL)	294,00	**352,80** BGN
	ACP	**Audio Control Panel,** front panel volume control & power switch to connects via RJ45 cable to active loudspeaker set; Dimensions (WxHxD): 85x85x28mm; Weight: 70g; Optional Build-in box : N-MODIN for brick walls & E-MODIN for dry walls	46,00	**55,20** BGN
	ACPR	**Audio Control Panel**, front panel mini jack & rear panel euroblock inputs, volume control and power switch, Connects via RJ45 cable to active loudspeaker set; Dimensions (WxHxD): 85x85x35mm; Weight: 75g; Optional Build-in box : N-MODIN for brick walls & E-MODIN for dry walls	67,00	**80,40** BGN
	ACPL	**Audio Control Panel,** front panel Mic/Line inputs, volume control & power switch, Connects via RJ45 cable to active loudspeaker set; Dimensions (WxHxD): 85x85x28mm; Weight: 90g; Optional Build-in box : N-MODIN for brick walls & E-MODIN for dry walls	67,00	**80,40** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
	NEW	**EN 54-24 CERTIFIED LOUDSPEAKERS**		
NEW	**EN-CM5T6**	**EN54-24 certified ceiling speaker with steel fire dome** 5.25" driver, Steel body and front grille, 1.5/3/6W 100 V; Frequency Response 320Hz - 19kHz; Sensitivity 93.5dB/1W/1m; Dimensions: Φ180x158mm, Mounting hole diameter: Φ172mm, IP50, white (RAL9010)	74,00	**88,80** BGN
NEW	**EN-CM6T6**	**EN54-24 certified ceiling speaker with steel fire dome** 6.5" driver, Steel body and front grille, 1.5/3/6W 100 V; Frequency Response 140Hz - 24kHz; Sensitivity 93.9dB/1W/1m; Dimensions: Φ220x137mm, Mounting hole diameter: Φ199mm, IP50, white (RAL9010)	70,00	**84,00** BGN
NEW	**EN-CMX6T10**	**EN54-24 certified 2-way ceiling speaker with steel fire dome** 6.5" woofer + 0.5" tweeter, Steel body and front grille, 1.5/3/6/10W 100 V; Frequency Response 70Hz - 24kHz; Sensitivity 89.2dB/1W/1m; Dimensions: Φ220x159mm, Mounting hole diameter: Φ203mm, IP50, white (RAL9010)	122,00	**146,40** BGN
NEW	**EN-SPH5T16-W**	**EN54-24 certified pendant sphere speaker** 5.25" driver, ABS body and front grille, 4/8/16W 100 V; Frequency Response 90Hz - 17kHz; Sensitivity 86.5dB/1W/1m; Outside Diameter: 185mm, white (RAL 9010)	171,00	**205,20** BGN
NEW	**EN-SPH6T20-W**	**EN54-24 certified pendant sphere speaker** 6.5" driver, ABS body and front grille, 2.5/5/10/20W 100 V; Frequency Response 90Hz - 20kHz; Sensitivity 93.5dB/1W/1m; Outside Diameter: 260mm, white (RAL 9010)	283,00	**339,60** BGN
NEW	**EN-SM6T10-W**	**EN54-24 certified metal on wall speaker** 6.5" driver, Steel body and front grille, 1.5/3/6/10W 100 V; Frequency Response 200Hz - 24kHz; Sensitivity 93.8dB/1W/1m; Dimensions (DxL): 170x75mm, IP54, white (RAL 9010)	101,00	**121,20** BGN
NEW	**EN-SMS6MT6-W**	**EN54-24 certified metal square on-wall loudspeaker** 6.5" driver, Steel body and front grille, 1.5/3/6W 100 V; Frequency Response 110Hz - 18kHz; Sensitivity 93.7dB/1W/1m; Dimensions (WxHxD): 252x192x82mm, IP54, white (RAL 9010)	122,00	**146,40** BGN
NEW	**EN-SMS6T6-W**	**EN54-24 certified MDF square on wall speaker** 6.5" driver, MDF body, steel front grille, 1.5/3/6W 100 V; Frequency Response 110Hz - 15kHz; Sensitivity 94.6dB/1W/1m; Dimensions (WxHxD): 252x192x82mm, IP54, white (RAL 9010)	95,00	**114,00** BGN
NEW	**EN-H10-G**	**EN54-24 certified compression driver horn speaker** UV and impact resistant ABS body, 1.25/2.5/5/10W 100 V; Frequency Response 370Hz - 13kHz; Sensitivity 98dB/1W/1m; Dimensions (DxL): 142x210mm, IP66, white (RAL 7035)	138,00	**165,60** BGN
NEW	**EN-H15-G**	**EN54-24 certified compression driver horn speaker** UV and impact resistant ABS body, 1.87/3.75/7.5/15W 100 V; Frequency Response 400Hz - 12kHz; Sensitivity 100.5dB/1W/1m; Dimensions (DxL): 209x272mm, IP66, white (RAL 7035)	159,00	**190,80** BGN
NEW	**EN-MP5T10-W**	**EN54-24 certified compact sound projector** 5.25" driver; aluminium body, steel grile, 5/10/15/20W 100 V; Frequency Response 130Hz - 19kHz; Sensitivity 91.2dB/1W/1m; Dimensions (DxL): 167x163mm, IP65, white (RAL9010)	199,00	**238,80** BGN
NEW	**EN-MP5T20-W**	**EN54-24 certified compact sound projector** 5.25" driver; aluminium body, steel grile, 1.5/3/6/10W 100 V; Frequency Response 120Hz - 23kHz; Sensitivity 92.1dB/1W/1m; Dimensions (DxL): 167x163mm, IP65, white (RAL9010)	212,00	**254,40** BGN
NEW	**EN-MPBD5T10-W**	**EN54-24 certified bi-directional sound projector** 2x5.25" drivers; aluminium body, steel griles, 1.5/3/6/10W 100 V; Frequency Response 145Hz - 17,5kHz; Sensitivity 94dB/1W/1m; Dimensions (DxL): 200x162mm, IP54, white (RAL9010)	219,00	**262,80** BGN
		OVO CABINET SERIES		
	OVO3-BL **OVO3-W**	Small design cabinet 2-way speaker, **3" coated paper cone woofer + 1" silk dome tweeter,** IP60, black or white Music Power: 40W 8Ohm; Freq. Response 90Hz-20kHz, Sensitivity 86dB/1W/1m, Dimensions (WxHxD): 110x160x117mm; Net Weight, pair: 1.9kg; Mounting bracket included **Priced per piece and sold in pairs only**	50,00	**60,00** BGN
	OVO3T-BL **OVO3T-W**	Small design cabinet 2-way speaker, **3" coated paper cone woofer + 1" silk dome tweeter,** IP60, black or white Music Power: 40W 16Ohm, 1.5/3/6W 100 V; Freq. Response 90Hz-20kHz, Sensitivity 86dB/1W/1m, Dimensions (WxHxD): 110x160x117mm; Net Weight, pair: 2.1kg; Mounting bracket included **Priced per piece and sold in pairs only**	60,00	**72,00** BGN
	OVO5-BL **OVO5-W**	Design cabinet 2-way speaker, **5.25" coated paper cone woofer + 1" silk dome tweeter**, IP40, black or white Music Power: 80W 8Ohm; Freq. Response 70Hz-20kHz, Sensitivity 91dB/1W/1m, Dimensions (WxHxD): 170x260x180mm; Weight: 2.45kg; Mounting bracket included, Incorporated free stand **Priced per piece and sold in pairs only**	80,00	**96,00** BGN
	OVO5T-BL **OVO5T-W**	Design cabinet 2-way speaker, **5.25" coated paper cone woofer + 1" silk dome tweeter**, IP40, black Music Power: 80W 16Ohm, 3/6/15/30W 100V; Freq. Response 70Hz-20kHz, Sensitivity 90dB/1W/1m, Dimensions (WxHxD): 170x260x180mm; Weight: 2.65kg; Mounting bracket included, Incorporated free stand **Priced per piece and sold in pairs only**	93,00	**111,60** BGN
	OVO5P-BL **OVO5P-W**	Design cabinet **Active** 2-way speaker set, **5.25" coated paper cone woofer + 1" silk dome tweeter**, IP40, black or white System performance: 2x20 W RMS; Freq. Response 50Hz-20kHz, THD:<0.03 % at full power -6 dB; S/N Ratio: >90dB Dimensions (WxHxD): 160x260x180mm; Weight: 2.65kg; Mounting bracket included, Incorporated free stand **Priced per piece and sold in pairs only**	222,00	**266,40** BGN
	OVO8-BL **OVO8-W**	Design cabinet 2-way speaker, **8" coated paper cone woofer + 1" silk dome tweeter**, IP40, black or white Music Power: 160W 8Ohm; Freq. Response 45Hz-20kHz, Sensitivity 93dB/1W/1m, Dimensions (WxHxD): 244x358x250mm; Weight: 6.1kg; Mounting bracket included, Incorporated free stand **Priced per piece and sold in pairs only**	172,00	**206,40** BGN
	OVO8T-BL **OVO8T-W**	Design cabinet 2-way speaker, **8" coated paper cone woofer + 1" silk dome tweeter**, IP40, black or white Music Power: 80W 16Ohm, 6/15/30/60W 100V; Freq. Response 45Hz-20kHz, Sensitivity 92dB/1W/1m, Dimensions (WxHxD): 244x358x250mm; Weight: 6.7kg; Mounting bracket included, Incorporated free stand **Priced per piece and sold in pairs only**	193,00	**231,60** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		MASK DESIGN SERIES		
	MASK2-BL **MASK2-W**	**2.5"** compact design cabinet loudspeaker, 50W 8Ohm (using a 150 Hz/12 dB/octave highpass filter), Freq. Response 120Hz-20kHz, Sensitivity 86dB/1W/1m, Dimensions (WxHxD): 82x94x108mm; Weight: 0.44kg; Mounting bracket included, IP50, black or white **Priced per piece and sold in pairs only**	56,00	**67,20** BGN
	MASK4-BL **MASK4-W** **MASK4-SLV**	2-Way design cabinet loudspeaker, **4.2" woofer + 1" silk dome tweeter**, IP64, black, white or silver Music Power: 70W 8Ohm; Freq. Response 80Hz-20kHz, Sensitivity 89dB/1W/1m, Dimensions (WxHxD): 129x223x130mm; Weight: 2.05kg; wall bracket and safety chain included **Priced per piece and sold in pairs only**	88,00	**105,60** BGN
	MASK4T-BL **MASK4T-W** **MASK4T-SLV**	2-Way design cabinet loudspeaker, **4.2" woofer + 1" silk dome tweeter,** IP64, black, white or silver Music Power: 70W 16Ohm, 2.5/5/10/20W 100V; Freq. Response 80Hz-20kHz, Sensitivity 89dB/1W/1m, Dimensions (WxHxD): 129x223x130mm; Weight: 2.05kg; wall bracket and safety chain included **Priced per piece and sold in pairs only**	101,00	**121,20** BGN
	MASK6-BL **MASK6-W**	2-Way design cabinet loudspeaker, **6" woofer + 1" silk dome tweeter**, IP64, black or white Music Power: 200W 8Ohm; Freq. Response 60Hz-30kHz, Sensitivity 92dB/1W/1m, Dimensions (WxHxD): 175x315x195mm; Weight: 3.4kg; wall bracket and safety chain included **Priced per piece and sold in pairs only**	141,00	**169,20** BGN
	MASK6T-BL **MASK6T-W**	2-Way design cabinet loudspeaker, **6" woofer + 1" silk dome tweeter**, IP64, black or white Music Power: 200W 16Ohm, 6/15/30/60W 100V; Freq. Response 65Hz-20kHz, Sensitivity 91dB/1W/1m, Dimensions (WxHxD): 175x315x195mm; Weight: 3.95kg; wall bracket and safety chain included **Priced per piece and sold in pairs only**	154,00	**184,80** BGN
	MASK8-BL **MASK8-W**	2-Way design wooden cabinet loudspeaker, **8" woofer + 1" silk dome tweeter**, IP40, black or white Music Power: 300W 8Ohm 100V; Freq. Response 60Hz-30kHz, Sensitivity 93dB/1W/1m, Dimensions (WxHxD): 250x411x250mm; Weight: 8.1kg; metal U-bracket included **Priced per piece and sold in pairs only**	326,00	**391,20** BGN
	NEW **MASK12-BL** **MASK12-W**	2-Way ful range loudspeaker, 12" woofer + 1,4" horn tweeter, IP40, black or white Dynamic Power: 700W 8Ohm Freq. Response 48Hz-22kHz, Sensitivity 98dB/1W/1m, Max SPL 127 dB, Dispersion angle: 90°H x 70°V Wooden cabinet, steel front grille, Dimensions (WxHxD): 370x628x370mm; Weight: 19kg;	863,00	**1.035,60** BGN
	NEW **MASK12T-BL** **MASK12T-W**	2-Way ful range loudspeaker, 12" woofer + 1,4" horn tweeter, IP40, black or white Rated Power: 120/240 W 100V, Freq. Response 48Hz-22kHz, Sensitivity 98dB/1W/1m, Max SPL 122 dB, Dispersion angle: 90°H x 70°V Wooden cabinet, steel front grille, Dimensions (WxHxD): 370x628x370mm; Weight: 19kg;	1.007,00	**1.208,40** BGN
	MASK2CMT-BL **MASK2CMT-W**	Ceiling mounting bracket for MASK2 black or white Length: 40mm; Weight: 30g, black	10,50	**12,60** BGN
	MASKL-BL **MASKL-W**	Pair of L-shaped side bracket for MASK 4/6 in black or white Dimensions: 185 mmx130 mm, 50 mmx130 mm; Weight: 1.05 Kg net per pair	35,00	**42,00** BGN
	MASKV-BL **MASKV-W**	V-shaped 2-way cluster bracket for MASK 4/6 in black or white Dimensions: 125 mmx70 mm (long sides) ,28 mmx70 mm (base); Weight: 0.3 Kg net per pcs	28,00	**33,60** BGN
	MASKW-BL **MASKW-W**	Double V-shaped 4-way cluster bracket for MASK 4/6 in black or white Dimensions: 125 mmx70 mm (sides), 155 mmx70 mm (base); Weight: 1 Kg net per pcs	43,00	**51,60** BGN
	NEW **MASK12PBRA-BL**	Pole mount bracket for MASK12 and MASK12T loudspeakers, black only Can be used with other compatible speakers up to 40 kg Dimensions (WxHxD): 130 x290x450 mm	132,00	**158,40** BGN
	NEW **MASK12UBRA-BL** **MASK12UBRA-W**	U bracket for MASK12-BL and MASK12T-BL, black or white special mounting system allows the installer to mount the loudspeaker in the correct position **Dimensions (WxHxD): 320x650x60 mm**	132,00	**158,40** BGN
		SUB SERIES		
	SUBLIME-BL **SUBLIME-W**	Ultra compact dual coil **passive 6.5" subwoofer**, 2x80W 2x8Ohm, black MDF cabinet, built in stereo crossover Frequency range with 2xMASK2: 50-20000Hz; System power with 2xMASK2: 2x120W @ 8Ω Sensitivity: 85dB (2.83V/1m); Max SPL: 105dB; Frequency Response: 50-200Hz Dimensions (WxHxD) 470x420x120mm; wall mounting brackets included, black or wite	312,00	**374,40** BGN
	SUBA165 **SUBA165-W**	**Active compact subwoofer, 8" subwoofer**, 140W, black MDF cabinet, active crossover, line or speaker level stereo input, adjustable low-cut SPL: 89dB (1W/1m); Max SPL: 109dB; Frequency Response: 30-180Hz (adjustable); Dimensions (WxHxD) 261x362x405mm; Weight: 12.7 kg, black or white	402,00	**482,40** BGN
	SUB2201-BL **SUB2201-W**	**Passive 10" subwoofer**, 250W 4Ohm, plywood construction, pole mount adaptor, black or whitre SPL: 96dB (1W/1m); Frequency Response: 45-150Hz Dimensions (WxHxD) 300x600x380mm; Weight: 18.5 kg	588,00	**705,60** BGN
	SUB2400-BL **SUB2400-W**	**Passive 2x10" subwoofer**, 2x400W 4 or 16Ohm, plywood construction, black or white SPL: 99dB (1W/1m); Max SPL: 133dB; Frequency Response: 45-150Hz Dimensions (WxHxD) 352x700x450mm; Weight: 30.4 kg	756,00	**907,20** BGN
		ELECTRONICS		
		MIXER AMPLIFIERS		
	CONCEPT1	**Integrated stereo amplifier 2x80W** 4 Ohm; 4 Line + 1 Mic inputs, RS232 & IR control, 1 or 2 zones paging; Operation modes: stereo / 2 zones linked / 2 individual zones; Digital limiter; Lo-cut filter; Automatic Loudness Source inputs with digital preset gain A-B-C-D: 5кOhm/0,3V , max 2,7V; Digital Bass & Treble tone control; Micro balanced Input: 1,5kOhm/1,5 mV, max 0,4V; Variable Pre-out & Line-out; Freq. Response: 10Hz-40kHz (- 0,5dB); THD: <0,05%; IMD: <0,09%; Noise A-weighted: >100dBA; Gain: 33dB; Damping Factor: >100 Protection systems : DC, temp, clip, overcurrent, short-circuit; Dimensions (WxHxD): 430x88x290mm; Weight : 6.6 kg	519,00	**622,80** BGN
	CONCEPT1T	**Integrated stereo amplifier 2x60W 100V**; 4 Line + 1 Mic inputs, RS232 & IR control, 1 or 2 zones paging; Operation modes: stereo / 2 zones linked / 2 individual zones; Digital limiter; Lo-cut filter; Automatic Loudness, Source inputs with digital preset gain A-B-C-D: 15кOhm/0,3V , max 2,7V; Digital Bass & Treble tone control; Micro balanced Input: 1,5kOhm/1,5 mV, max 0,4V; Variable Pre-out & Line-out; Freq. Response: 10Hz-40kHz (- 0,5dB); THD: <0,05%; IMD: <0,09%; Noise A-weighted: >100dBA; Gain: 33dB; Damping Factor: >100 Protection systems : DC, temp, clip, overcurrent, short-circuit; Dimensions (WxHxD): 430x88x290mm; Weight : 6.6 kg	633,00	**759,60** BGN
	CONCEPT1-RC	Infrared remote control for Concept 1 and Concept 1T	30,00	**36,00** BGN
	CONCEPT1T-KIT	2x100V transformers, 6 Watts each. Transforms CONCEPT1 into CONCEPT1T	116,00	**139,20** BGN
	MA35	**Compact mixer amplifier 35W 100V**, 3 mic + 2 line inputs, chime, 2-level priority, Speaker outputs: 8 Ohm, 70 - 100 V; Pre amp out; Record out; Chime; Limiter; Bass & Treble tone controls; 2-step priority mute system (MIC1 VOX / contact closure); Frequency Range: 60Hz-18kHz; S/N Ratio: -77dB; Distortion : <0.5%; 24V DC / 230V AC mains power Dimensions (WxHxD): 272x88x286mm; Weight: 5 kg	325,00	**390,00** BGN
	MA65	**Compact mixer amplifier 65W 100V**, 3 mic + 2 line inputs, chime, 2-level priority Speaker outputs: 8 Ohm, 70 - 100 V; Pre amp out; Record out; Chime; Limiter; Bass & Treble tone controls; 2-step priority mute system (MIC1 VOX / contact closure); Frequency Range: 60Hz-18kHz; S/N Ratio: 77dB; Distortion : < 0.5%; 24V DC / 230V AC mains power Dimensions (WxHxD): 272x88x286mm; Weight: 6.4 kg	467,00	**560,40** BGN
	MA35-19	19" brackets for MA35 and MA65 mixing amplifiers Material : Metal; Black; Dimensions (HxWxD): 88x104x50 mm; Weight : 0.4 Kg	14,20	**17,04** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
	MA125	**Mixer amplifier 120W 100V**, 4 mic + 4 line inputs, 3 level priority, chime, 24V overide output Speaker outputs: 8 Ohm, 50 - 70 - 100 V; Pre amp out; Ampi In; Record out; Chime; Limiter; Bass & Treble tone controls; 3-step priority mute system (Emergency / MIC1 VOX / contact closure); Frequency Range: 40Hz-22kHz; S/N Ratio: >95dB; Distortion : < 0.5%; 24V DC / 230V AC mains power Dimensions (WxHxD): 483x88x230mm; Weight: 9kg	637,00	**764,40** BGN
	MA200	**Mixer amplifier 200W 100V**, 4 mic + 4 line inputs, 4 zones, chime, 3-level priority, 24V override Speaker outputs: 8 Ohm, 50 - 70 - 100 V; Pre amp out; Amp In; Record out; Chime; Limiter; Bass & Treble tone controls; 3-step priority mute system (Emergency / MIC1 VOX / contact closure); Frequency Range: 40Hz-25kHz; S/N Ratio: >95dB; Distortion : <0.3%; 24V DC/230V mains power Dimensions (WxHxD): 483x88x356mm; Weight: 12.1kg	1.023,00	**1.227,60** BGN
	MA200CDR	**Mixer amplifier 200W 100V** with AM/FM Tuner & CD/MP3; 4 mic + 4 line inputs, 4 zones, chime, 3-level priority, 24V override Speaker outputs: 8 Ohm, 50 - 70 - 100 V; Pre amp out; Amp In; Record out; Chime; Limiter; Bass & Treble tone controls; 3-step priority mute system (Emergency / MIC1 VOX / contact closure); Frequency Range: 40Hz-25kHz; S/N Ratio: >95dB; Distortion : <0.3%; 24V DC/230V mains power Dimensions (WxHxD): 483x88x356mm; Weight: 13.5kg	1.778,00	**2.133,60** BGN
	MA247	**Multizone Mixing amplifier, 6 Zone (1 passive, 5 active) 100v/240 watt**, volume control per zone, selective paging possible, different source for zone 1 and zones 2-6, 1xPaging mic, 3xMic/Line and 4xLine inputs, 24V overide priority output per zone. External paging amplifier output and input, 24V DC 230V AC mains power, Dimensions (WxHxD): 483x88x360mm; Weight: 13.6kg	1.502,00	**1.802,40** BGN
	MA247MR	**Multizone Mixing amplifier, 6 Zone (1 passive, 5 active) 100v/240 watt**, volume control per zone, selective paging possible, different source for zone 1 and zones 2-6, 1xPaging mic, built-in FM/AM tuner and media player, MP3 from USB stick, SD and MMC cards3xMic/Line and 2xLine inputs, 24V overide priority output per zone. External paging amplifier output and input, 24V DC 230V AC mains power, Dimensions (WxHxD): 483x88x356mm; Weight: 14.4kg	1.940,00	**2.328,00** BGN
		## *MICROPHONES*		
	MICPAT-D	**Paging Uni-directional microphone** with gooseneck & priority switch, DIN5 connector Frequency Range: 80Hz-12kHz; Sensitivity: -70dB@1kHz; Rated output impedance : 600 Ohm Cable type: 2 core + 2 core screened, 3m length, 5-pole DIN connector; One piece mold, aluminium base; Toggle switch: Talk-OFF-Continuous Talk; Weight (incl. cable): 0.81 kg	120,00	**144,00** BGN
	MICPAT-2	**2-Zone paging microphine with gooseneck for use with CONCEPT1, MA247 and MA247MR** Polar Pattern : Uni-directional; Frequency Range: 80Hz-12kHz; Sensitivity: -70dB@1kHz, Rated output impedance : 600 Ohm; 2 push-to-talk buttons; One piece mold, aluminium base; Cable type: 2 core + 2 core screened, 3 m - open wire; Weight (incl. cable): 0.81kg	173,00	**207,60** BGN
	MICPAT-4	**4-Zone paging microphone with gooseneck for use with Zone 4** Directional, low feedback, electret capsule; Frequency Range: 80Hz-20kHz, Output level: 2V; Output impedance: 50 Ohm; Balanced line out; bus system connection; Cable supplied: CAT5 5m; Weight (without cable): 0.550 kg; Color: grey Dimensions (base unit) mm: 115(W)x162(D)x60 (H); Gooseneck length: 275 mm	493,00	**591,60** BGN
	MICPAT-6	**6-Zone paging microphine with gooseneck for use with MA247/MA247MR** Polar pattern : Directional, low feedback, electret capsule; Frequency range: 80Hz-20kHz, Rated output level: 2V balanced line output; Rated output impedance: 50Ohm, Connection : bus system accepts multiple units in parallel; CAT5 cable 5m terminated with RJ45 connector (supplied) Dimensions base (WxHxD): 115x162x60mm; Gooseneck length: 275mm; Weight: 0.55kg; Grey color	537,00	**644,40** BGN
		## NEW *DISSCUSSION SYSTEM*		
	NEW **MDS.CHAIR**	**Chairman Microphone for Microphone discussion system** Unidirectional condensor microphone; Frequency Response 80Hz-16kHz; Maximum SPL: 100 dB for 1% THD; RJ45 - CAT5 system interconnection cables; Dimensions with mic (HxWxD): 494x110x165 mm, Net Weight: 0,73 kg;	302,00	**362,40** BGN
	NEW **MDS.DEL**	**Delegate Microphone for Microphone discussion system** Unidirectional condensor microphone; Frequency Response 80Hz-16kHz; Maximum SPL: 100 dB for 1% THD; RJ45 - CAT5 system interconnection cables; Dimensions with mic (HxWxD): 494x110x165 mm, Net Weight: 0,73 kg;	221,00	**265,20** BGN
	NEW **MDS.INT**	**Interface and PSU for Microphone discussion system** System signal output: unbalanced 6.3 mm jack; Nominal output level: 100 mV, Output impedance < 1 kOhm; S/N Ratio: >60 dB; Interface Dimensions (HxWxD): 24x49x49 mm, Interface Net Weight: 36g; PSU - 15 VDC/4,3A switching mode power supply	168,00	**201,60** BGN
		## *PRE-AMPLIFIERS*		
	PM7400MKII	**Stereo pre-amplifier/mixer,** 6 stereo line inputs, 2 mic inputs with phantom, 2 stereo output zones; mute contact Frequency Response: 20Hz-25kHz; Distortion: < 0.01%; 3-band MIC tone control & 3-band Music tone control; Dimensions (WxHxD) : 483x44x275mm; 1U 19" rackmount; Weight: 3.1 kg	493,00	**591,60** BGN
	ZONE4	**Quad zone pre-amplifier:** 4 stereo output zones. Inputs: 3 mono mic/line + 4 stereo line inputs Freq. response: 20Hz-30kHz; Noise: >90dB; THD: <0,02%; Crosstalk: >75dB; Max nominal gain: +5dB; Max output voltage : +13dBV, 4.5V; bass & treble controls; phantom power mic 2/3, Dimensions WxHxD: 420x44x190mm; Weight: 2.5kg; Remote Control: via RJ45 CAT-5 per zone; Optional remote control panel: ZONE4R	1.126,00	**1.351,20** BGN
	ZONE4R	**Remote control panel for the APart's multifunctional 4-zone pre-amplifier ZONE4.** Music level control, source selection and microphone mix level control. Clear digital display for monitoring of the unit. Standart CAT5 or CAT6 cables only, max. 100 m per zone. Front plate dimensions: 114x80 mm, Cutout dimensions without back box : 70x55mm; Mounting depth : 40mm	173,00	**207,60** BGN
	RJ45SPLIT	**RJ45 splitter** 1 input, 4 output to connect multiple MICPAT-4 or ZONE4R to ZONE4	97,00	**116,40** BGN
	PM1122	**Stereo pre-amplifier/mixer**, 4 stereo line inputs, 5 mic/line imputs, 2 stereo zones, 1U 19" rack mounting, black Freq. response: 20Hz-22 kHz; Noise: >93dB; THD:< 0,008%; Crosstalk: >70dB; Max nominal gain : +6dB Max output voltage: 9 V; Insert PCB for optional signal-processing; 2-tone Chime; 4-level priority system Bas & Treble tone controls zone 1 & 2; Music & micmix level control; Balanced mic/line inputs with Phantom power; Link input & Link ouput; Dimensions LxWxH: 430x245x44 mm, 1U 19" rackmount; Weight: 2.8 kg	744,00	**892,80** BGN
	NTM-1	Groundloop transformer Balanced microphone transformer for the PM1122 pre-amplifier	120,00	**144,00** BGN
	PM1122-INT	**Optional digital RS232 interface for PM1122** Controls the 4 sources, the music level and the microphone level via CAT5 cable. 3 possible ways to control the interface remotely: by RS-232; using contacts to recall presets and by using an RF wall controller in combination with a remote controlled RF-module, plugged into the back of a PM122-INT. Dimensions WxHxD: 198x45x90mm	294,00	**352,80** BGN
	PM1122WR	**Optional wireless remote control receiver for RF-extension of the PM1122-INT** Work exclusively with the wireless controllers (PM1122W) and digital remote interface (PM1122INT) of the PM1222, APart's 2-stereo zone, and remote controlled pre-amplifier. Both the wireless controllers and the receiver operate on the 863.3 Mhz band. Dimensions WxHxD: 39x52x37mm	217,00	**260,40** BGN
	PM1122R	**Optional remote panel for PM1122** with music selection, music volume and mic mix volume Music & MicMix level control: 0-10V operated; Music Selector control: DC operated Power supply: only via RJ-45 / CAT-5 to PM1122 main unit Dimensions HxW: 80x115 mm (40mm depth behind panel); Weight : 165g; Optional BBI1 built-in box & BB1 onwall box	69,00	**82,80** BGN
	PM1122RL	**Optional remote panel for PM1122** - music selection, music volume & micmix volume, mic & line inputs with tone controls Power supply: only via RJ-45/CAT-5 to PM1122 main unit, Line input: Freq. response: 20Hz-22kHz; 250mV; 17kOhm Max input level: -3dBV; S/N Ratio: >80dB; THD: <0,09%, Mic input: Freq. response : 100Hz-20kHz; 3mV; 1.2 kOhm; S/N Ratio : >75dB; THD: < 0,15%; Phantom power: 20V Dimensions HxW: 93x101mm (40mm depth behind panel); Weight : 260g Optional BBI2 built-in box & BB2 onwall box	100,00	**120,00** BGN
	PM1122W-BL **PM1122W-W** **PM1122W-SLV**	**Optional ultra-thin wireless remote control for the PM1122**, APart's multifunctional 2-stereo zone pre-amplifier. music source, Music volume and mic mix volume control, black Dimensions : 85x85x15 mm	329,00	**394,80** BGN
	BB1	On-wall box for the PM1122R and ZONE4R remote controls Dimensions: 80x114x48 mm (HxWxD)	26,00	**31,20** BGN
	BB2	Build on box white for remote panel with input PM1122RL, the analog remote controls of the PM1122 pre-amplifier Dimensions: 116x116x56 mm (HxWxD)	64,00	**76,80** BGN
	BBI1	Universal build in box BTicino 3 modules; In-wall back box for the PM1122R and ZONE4R remote controls Dimensions: 80x115 mmx40 mm (HxWxD)	3,10	**3,72** BGN
	BBI2	Universal BTicino built in box 2x3 modules; In-wall back box for the PM1122RL, the analog remote controls of the PM1122 pre-amplifier Dimensions: 93x101 mmx40 mm (HxWxD)	9,70	**11,64** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		POWER AMPLIFIERS		
	CHAMP-2	**High End 2 channel power amplifier 2x350W 4Ohm**, Bridge 750W 8Ohm, Convectional cooling, no fan; High current, high voltage class G power amp design; Balanced (XLR) & Unbalanced (RCA) inputs; Frequency response: 10Hz-50kHz; THD: < 0.05; IMD <0.06%; Noise >100dBA; Gain 30dB (36dB bridged), Damping factor >200; Dynamics & level control APC, switchable for 2-3 or 4-8 ohms; Efficiency: 70%, Protection circuits DC, HF, clip, overcurrent, short-circuit, temperature Dimensions (WxHxD) 483x44x360mm 1HU; Weight 7.5 kg; black	779,00	**934,80** BGN
	CHAMP-3D	**2 input 3 output digital amplifier, SUB:1x1340W 2Ohm, TOP: 2x522W 2.7Ohm**; Convection cooled, class D Hypex amplifers, Full DSP incl.speaker wizard, crossover, EQ, delay and dynamics processor.; Balanced inputs: XLR & Euroblock, Frequency response: 10Hz-24kHz; THD: < 0.1; IMD <0.06%; S/N Ratio: >90dBA Damping factor >400; Dynamics and level control APC; Protection circuits DC, HF, clip, overcurrent, short-circuit, temperature Dimensions (WxHxD): 483x89x380mm 2HU; Weight: 16 kg, black	1.826,00	**2.191,20** BGN
	CHAMP-4	**High End, 4 channel power amplifier 4x125W 4Ohm,** Bridge 230W 8Ohm; convectional cooling; Class AB power amp circuit design; Unbalanced (RCA) inputs; Frequency response: 20Hz-40kHz; THD: < 0.15; IMD <0.15%; Noise >100dBA; Gain 26dB (32dB bridged), Damping factor >100; Dynamics and level control APC, switchable for 2-3 or 4-8 ohms; Efficiency: 70%, Protection circuits DC, HF, clip, overcurrent, short-circuit, temperature Dimensions (WxHxD) 483x44x360mm 1HU; Weight 7.5 kg; black	806,00	**967,20** BGN
	PA240P	**Power amplifier 240W 100V** with program & priority input, 24V output, tone control, 24V DC - 230 V AC Balanced Adjustable Program & Priority Inputs; Loudspeaker outputs: channel 1 & 2: 4Ohm - 50V - 70V - 100V, Priority output: 2x24V; Bass & Treble Tone control, Frequency response: 35Hz-22kHz; S/N Ratio: >95dB; THD: <0.5%; Dimensions (WxHxD): 430x88x366mm (Detachable 19" brackets included); Weight: 14.1kg	816,00	**979,20** BGN
	PA2240BP	**2 channel 100V power amplifier, 2x240W**, 480W bridge, Balanced Adjustable Program & Priority Inputs per channel; Loudspeaker outputs: channel 1 & 2: 4Ohm - 50V - 70V - 100V, Priority output: 2x24V; Bass & Treble Tone controls, 230V AC & 24V DC, Frequency response: 35Hz-22kHz; S/N Ratio: >95dB; THD: <0.5%; Dimensions (WxHxD): 430x88x412mm (Detachable 19" brackets included)); Weight: 21.7kg	1.339,00	**1.606,80** BGN
	REVAMP2250	**2-channel power amplifier, 2x250W 4Ohm**, Bridge 1x500W 8Ohm, Class D, convectional cooling, Built-In DSP Input Sensitivity: 0 dBV / 1 Vrms; Channel separation: > 74 dB @ Full power, 1kHz; S/N Ratio:> 90 dB @ Full power, A-weighted Balanced Euroblock & Unbalanced RCA inputs; Pass-Through RCA-otputs, Output connections: Euroblock & SpeakOn Automatic Limiting System APC (patent pending)	836,00	**1.003,20** BGN
	REVAMP2600	**2-channel power amplifier, 2x600W 4Ohm**, Class H, Built-In DSP Input Sensitivity: 0 dBV / 1 Vrms; Channel separation: > 74 dB @ Full power, 1kHz; S/N Ratio:> 90 dB @ Full power, A-weighted Balanced Euroblock & Unbalanced RCA inputs; Pass-Through RCA-otputs, Output connections: Euroblock & SpeakOn Automatic Limiting System APC (patent pending)	1.002,00	**1.202,40** BGN
	REVAMP1680	**16-channel power amplifier, 16x80W 4Ohm**, 8x160W 8Ohm, flexible input routing, channel bridging, convectional cooling Input Sensitivity: -6 dBV / 0,5 Vrms; Channel separation: >68 dB @ Full power, 1kHz; S/N Ratio:> 98 dB @ Full power, A-weighted Line input(s) unbalanced: 16 RCA + 2 stereo buses RCA + 2 stereo buses outputs RCA; Output connections: Euroblock Audio trigger 10mVrms, External trigger 3-30V AC/DC	2.090,00	**2.508,00** BGN
	REVAMP4120T	**4-channel power amplifier, 4x120W 35/5070/100V**, Bridge 2x240W 4Ohm 70/100V, Class D Input Sensitivity: 0 dBV / 1 Vrms; Channel separation: > 68 dB @ Full power, 1kHz; S/N Ratio:> 101 dB @ Full power, A-weighted Balanced Euroblock & Unbalanced RCA inputs; Pass-Through RCA-otputs; Hi-Pass Filter 250Hz	1.453,00	**1.743,60** BGN
	REVAMP4240T	**4-channel power amplifier, 4x240W 35/5070/100V**, Bridge 2x480W 4Ohm 70/100V, Class D Input Sensitivity: 0 dBV / 1 Vrms; Channel separation: > 68 dB @ Full power, 1kHz; S/N Ratio:> 101 dB @ Full power, A-weighted Balanced Euroblock & Unbalanced RCA inputs; Pass-Through RCA-otputs; Hi-Pass Filter 250Hz	1.895,00	**2.274,00** BGN
		MUSIC SOURCES & SOUND SYSTEMS		
	PC1000RMKII	**Media Player, CD/MP3 from Disc, SD-card or USB memory stick,** RS232 control, IR remote included. Compatible media: Audio CD, CDR, CDRW, DVD, DVDR, DVDRW; Flash memory sticks & cards up to 32 GB; FAT32. Audio format: MP3 32-320 kbps & VBR, WMA; Balanced & Unbalanced Line out: 1.9V adjustable; Output impedance: <1kΩ SPDIF outputs (Toslink & Coax): S/N Ratio: >90dB; THD: <0.05%; Dimensions: 430 (482)x305 (315)x44 mm; Weight: 4.5Kg	418,00	**501,60** BGN
	PCR3000RMKII	**DAB/FM RDS Tuner, CD/MP3 from Disc, SD-card or USB memory stick**, RS232 control, IR remote included RS232 or IR remote control (included); Combined and individual output with gain control for tuner and CD/MP3 section Coaxial and optical digital audio output for CD section Dimensions : 44 (h)x483 (w)x280 (d) mm	736,00	**883,20** BGN
	PCD-REM	Optional remote control for DVD control functionality on PC1000RMKII and PCR3000RMKII	28,00	**33,60** BGN
	NEW **PMR4000RMKII**	**Professional multi source music player with internet radio, UPnP and USB media player and integrated FM RDS Tuner.** FM Radio; internet radio; USB-Drive, UPnP; Supported audio codes (MP3,WMA,FLAC,WAV,ID3 tags support) Wired and Wi-Fi 2.4G Ethernet access; Analog output with level control and optical digital output ; IR Remote Control included; Dimensions (LxWxH): 484(430)x325(300)x44mm; Weight 3.85kg	713,00	**855,60** BGN
	PR1000R	**Professional AM/FM RDS radio tuner**, RS232 control, RDS data available via RS232, handheld remote, FM antenna & removable rack ears included, 1U 19" rackmount, 40 Presets; Adjustable audio output level Dimensions LxWxH : 484 (430)x270 (245)x44 mm 1U 19" rackmount; Weight : 2.8 kg	409,00	**490,80** BGN
	PR4000R	**Professional 4xAM/FM RDS radio tuner**, RS232 control, RDS data available via RS232, handheld remote, FM antenna & removable rack ears included; Presets per tuner: 4x10; Adjustable audio output level: 4 stereo outs; Dimensions LxWxH : 484 (430)x270 (245)x44 mm 1U 19" rackmount; Weight : 2.8 kg	937,00	**1.124,40** BGN
	DAB-FM	**DAB & FM combiner** Allows the use of cable distribution combined with a DAB air antenna	54,00	**64,80** BGN
		DSP POWERED AUDIO MATRIX		
	AUDIOCONTROL 12.8	**Digital Matrix 12 Audio inputs – 8 Audio outputs** Audio & Control processing; Paging possibilities; RS232 serial control; Configurable control functions; Built-in real time clock scheduler;Graphical Installer Interface (GII); Fixed architecture DSP platform; Macro programming; Fully programmable DIMIC1 and DIMIC12(S) digital paging stations; Fully programmable DIWAC (digital wall mount controller) Designed by Apart Audio in Belgium and manufactured in Europe; Dimensions: 483 (w) x 44 (h) x 310 (d) mm, Weight: 3.8 kg	2.223,00	**2.667,60** BGN
	AC12.8FP	**Features Pack for AUDIOCONTROL12.8** Message Player / Recorder for up to 8 messages; Logical Inputs / 0-10V inputs; Logic Outputs; Output Delay, Zone Combining	620,00	**744,00** BGN
	AC12.8SET	**Combination of AUDIOCONTROL12.8 matrix and AC12.8FP Extra Features Pack**	2.703,00	**3.243,60** BGN
	DIPEX	**Digital Priority/Emergency Extender for AUDIOCONTROL12.8** DIPEX allows to connect message players or to make a connection with EVAC/Alarm centrals to produce evacuation messages or alarm signals. When the DIPEX is triggered, the line level signal will go into the AUDIOCONTROL12.8 via the DIMIC paging bus. The priority level of DIPEX can be set between 0 and 7. The 'priority zero' has absolute priority. DIPEX allows paging via the telephone central or to create an overall mute contact for the AUDIOCONTROL12.8.	390,00	**468,00** BGN
	NEW **AUDIOSYSTEM8.8**	**Audio matrix 8 inputs & 8 outputs, 8x30W amplifiers, 4 built-in FM tuners** 8 speaker outputs (4 stereo or 8 mono zones) each with built-in 30 watts amplifier; 4 additional line outputs; 4 FM radios built-in; 4/8 stereo/mono line inputs; All call paging microphone input; Prority input; Integrated web server based GUI for configuration and/or control. DIWAC wall panels for remote control; Dimensions: 483 (w) x 44 (h) x 308 (d) mm, Weight: 3.8 kg; Made in Belgium;	2.678,00	**3.213,60** BGN
	DIMIC1	**Digital ALL CALL Paging Station** for use with AUDIOCONTROL12.8 Configuration via the host's graphical user interface. All zone selection button. Flexible microphone stem. Speech-optimized DSP. PTT button; Paging status LED; Nominal output level: 775 mV; Nominal sensitivity: 85 dB SPL; Max SPLI: >110 dB SPL; THD: typical <0.5%; Frequency Response -3 dB: 220 – 20000 Hz (speech filter); Lo-cut: 220 Hz, 6 dB/oct Dimensions base (w x d x h): 110 x 240 x 58 mm; Mic stem length including mic and windscreen: 395 mm	380,00	**456,00** BGN
	DIMIC12	**Digital Paging Station** for use with AUDIOCONTROL12.8 Configuration via the host's graphical user interface. 12 selection buttons and status LEDs. Flexible microphone stem. Speech-optimized DSP. PTT button; Nominal output level: 775 mV; Nominal sensitivity: 85 dB SPL; Max SPLI: >110 dB SPL; THD: typical <0.5%; Frequency Response -3 dB: 220 – 20000 Hz (speech filter); Lo-cut: 220 Hz, 6 dB/oct Dimensions base (w x d x h): 110 x 240 x 58 mm; Mic stem length including mic and windscreen: 395 mm	683,00	**819,60** BGN
	DIMIC12S	**Digital Paging Station** (slave unit) to connect with DIMIC12. 12 selection buttons and status LEDs. Easy to configure via the host's graphical installer interface. All buttons can be programmed to page a zone, select a source, control the volume, recall a preset, trigger a macro or even do control functions of other devices like a CD player for example. Up to 7 DIMIC12S expansions per one DIMIC 12 for a total of 96 programmable buttons available. Dimensions (w x d x h): 110 x 240 x 58 mm	339,00	**406,80** BGN
	DIWAC	**Digital programmable wall control** for AUDIOCONTROL12.8 Source selection and volume adjustment buttons, 2 line - 12 character LCD display with a timed (time adjustable) white backlight. Dimensions: 83 x 83 x 9 mm; Cut-out dimensions: approx. 51 mm diameter or 51x51mm min. Mounting depth: min. 20 mm Fits in: E-MODIN and N-MODIN; Weight: 72 g including wall mount chassis	172,00	**206,40** BGN
	NEW **ALINP**	**Active local input panel** Line and Microphone inputs both with individual volume control ALPS Push lock buttons, built in mixer-preamplifier For use with AUDIOCONTROL12.8, PM1122, ZONE4 and MA247/MR or any other device with Line or MIC/LINE input with 24V phantom power Dimensions: 83 x 83 mm x 30 mm Fits in: E-MODIN and N-MODIN	183,00	**219,60** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		VOLUME CONTROLS		
		MULTI-CHANNEL SERIES		
	19-VOL6120	Rack mount unit with 6x120W 100V volume controls, wiith 24V priority relays, Attenuation Steps: 11 + "0"; Weight: 3.61 kg; Dimensions : 88x483x230 mm (HxDxW), 2U height	501,00	**601,20** BGN
	19-VOL660	Rack mount unit with 6x60W 100V volume controls, wiith 24V priority relays, Attenuation Steps: 11 + "0"; Weight: 3.61 kg; Dimensions : 88x483x230 mm (HxDxW), 2U height	370,00	**444,00** BGN
	SVC4	4-zone stereo volume control, 6 steps + on/off switch, max. power of the connected speakers: 4x(2x40) W Loudspeakers Impedance: for 2 zones - 8 Ohms; for 3 and 4 zones - 16 Ohms Weight: 1,1 kg; Dimensions : 46x210x185 mm (HxDxW)	208,00	**249,60** BGN
		EURO SERIES		
	E-VOL20 **E-VOL20-BL**	100 Volt volume control EURO, 20W with 24V priority, white or black Attenuation steps: 11 + "0"; Dimensions (WxHxD): 80x80x45mm; Weight: 104g Optional Build-in box : E-MODIN & Build-on box : E-MODON	23,00	**27,60** BGN
	E-VOL40	100 Volt volume control EURO, 40W with 24V priority, white Attenuation steps: 11 + "0"; Dimensions (WxHxD): 80x80x50mm; Weight: 234g Optional Build-in box : E-MODIN & Build-on box : E-MODON	46,00	**55,20** BGN
	E-VOL60	100 Volt volume control EURO, 60W with 24V priority, white Attenuation steps: 11 + "0"; Dimensions (WxHxD): 80x80x50mm; Weight: 236g Optional Build-in box : E-MODIN & Build-on box : E-MODON	60,00	**72,00** BGN
	E-VOL120	100 Volt volume control EURO, 120W with 24V priority, white Attenuation steps: 11 + "0"; Dimensions (WxHxD): 80x80x50mm; Weight: 336g Optional Build-in box : E-MODIN & Build-on box : E-MODON	73,00	**87,60** BGN
	E-VOLST **E-VOLST-BL**	Stereo volume control EURO, 2x40W, 4-16 Ohm, white or black Attenuation steps: 10; Dimensions (WxHxD): 80x80x60mm; Weight: 278g Optional Build-in box : E-MODIN & Build-on box : E-MODON	89,00	**106,80** BGN
		NIKO SERIES		
	N-VOL30-W **N-VOL30-BL** **N-VOL30-SLV**	100V volume controller NIKO, 30W/24V Intense Faceplate,White, Anthracite, Sterling Attenuation steps: 10 + "0"; Dimensions (WxHxD): 90x90x85mm; Weight: 150g Optional Build-in box : E-MODIN & Build-on box : E-MODON	159,00	**190,80** BGN
	N-VOL30-WO **N-VOL30-CO**	100V vulume controller NIKO, 30W/24V Original Faceplate, White or Creme Attenuation steps: 10 + "0"; Dimensions (WxHxD): 90x90x85mm; Weight: 150g Optional Build-in box : E-MODIN & Build-on box : E-MODON	145,00	**174,00** BGN
	N-VOLST-W **N-VOLST-BL** **N-VOLST-SLV**	Stereo volume controller NIKO; 2x20W 4-8-16Ohm, Intense Faceplate, White, Anthracite & Sterling Attenuation steps: 5 + "0"; Dimensions (WxHxD): 90x90x85mm; Weight: 150g Optional Build-in box : E-MODIN & Build-on box : E-MODON	159,00	**190,80** BGN
	N-VOLST-WO **N-VOLST-CO**	Stereo volume controller NIKO, 2x20W 4-8-16Ohm, Original Faceplate, White or Creme Attenuation steps: 5 + "0"; Dimensions (WxHxD): 90x90x85mm; Weight: 150g Optional Build-in box : E-MODIN & Build-on box : E-MODON	145,00	**174,00** BGN
	N-VOL10K-W **N-VOL10K-BL**	Remote controller NIKO 10K, Intense Faceplate, White or Anthracite Impedance: 10kΩ; Regulation: linear ;Dimensions (WxHxD): 90x90x85mm; Optional Build-in box : E-MODIN & Build-on box : E-MODON	145,00	**174,00** BGN
	N-MODIN	N-MODIN is a Helia build-in box for ACP,ACPL, ACPR, DIWAC and Niko volume controls.	4,60	**5,52** BGN
	E-MODIN	The E-MODIN in-wall back box can be used with the ACP, ACPL, ACPR, DIWAC and the Apart E-VOL volume controls (E-VOL20, E-VOL40 and E-VOL60). Diameter: 70 mm, Depth: 60 mm, Color: bright orange, polypropylene plastic	6,20	**7,44** BGN
	E-MODON	Surface mounting box Apart volume controls (E-VOL20, E-VOL40, E-VOL60, E-VOL120 and E-VOLST). Dimensions: 83 (H)x83 (W)x50 (D) mm Color: white; Material: plastic	12,30	**14,76** BGN
		ACCESSOIRES		
	BUZZSTOP-MKIII	Universal stereo input adaptor, converts any output to line level. Converts 100V to low impedance, provides isolation to avoid ground loops; Balanced & Unbalanced Line Level Inputs; PA Amp Input: 100V-70V-33V; Low Imp Amp Input, 8Ohm amp; Telephone Input; Balanced & Unbalanced Outputs; Black metal housing; Dimensions (WxHxD): 241x44x72мм; Weight: 0.5 kg	97,00	**116,40** BGN
	IMPMET	Professional audio impedance meter; 3 1/2 digit LCD display with data hold, low battery and measured units indication Included accessories: test leads with separate alligator clips, 6xAA batteries, soft bag and user manual Basic accuracy: +- 2% + 2 digits at 18 to 28°C and relative humidity <75%. Test frequency: approx. 330 Hz Dimensions (LxWxH): 168x110x62mm; Weight: 500 g	320,00	**384,00** BGN
	NETKIT-IR	Ethernet to IR convertor; 100/10 MBits Ethernet Network connection - TCP, DHCP & HTTP standards 3 selectable IR outputs or sensor inputs; 3 IR emitters & 1 IR receiver for IR-learning included, Integrated web server; Power Input: 5 to 16V DC@300mA (power adapter included), Aluminum housing, Dimensions (LxWxH): 82.5x57x32mm; Weight: 92 g	386,00	**463,20** BGN
	NETKIT-RS	Ethernet to RS-232 convertor; Male DB9 Connector; 1200 to 115.000 baud data rates; Odd, Even, and None parity Bi-directional hardware RTS/CTS flow control; 100/10 MBits Ethernet - TCP, DHCP & HTTP, Integrated web server; Power Input: 5 to 16V DC@300mA (power adapter included), Aluminum housing, Dimensions (LxWxH): 82.5x57x32mm; Weight: 92 g	386,00	**463,20** BGN
	BUZZ19	Metal adapter for 2 pieces Buzz-StopII in 19" Rack	10,50	**12,60** BGN
	CE2E2	(A) Cable 1.5m euro connector 2P to euro 2P	17,40	**20,88** BGN
	CE3E3	(B) Cable 1.5m euro connector 3P to euro 3P	19,30	**23,16** BGN
	CE3RY	(E) 5m euro connector 3P to RCA MALE Y-Split	20,00	**24,00** BGN
	CE3XM	(C) Cable 1.5m euro connector 3P to XLR Male 3P	19,30	**23,16** BGN
	CMJRY	(K) Cable 1.5m 3.5mm stereo mini-jack to 2x RCA female	23,00	**27,60** BGN
	CRYRY	(F) Cable 1.5m RCA to RCA	12,70	**15,24** BGN
	CXFRY	(G) 5m XLR Female 3P to 2 RCA male/female	18,80	**22,56** BGN
	CXFXM	(D) Cable 2m XLR Female 3P to XLR Male 3P	52,00	**62,40** BGN
	SAFCAB6	safety cable for cabinet speakers up to 6" (per PAIR)	9,30	**11,16** BGN
	STFLOOR	Floorstand for loudspeaker with pole adapter	67,00	**80,40** BGN
	STSUB	Pole stand for mounting of MASK8 or MASK8F onto SUB with pole adapter	34,00	**40,80** BGN
	STT	T-adapter for 2 pieces MASK8 or MASK8F on one STFLOOR or STSUB	139,00	**166,80** BGN
	T20	8 Ohm to 100V transformer with different power taps: 20 - 10 - 5 - 2.5 watt	19,30	**23,16** BGN
	T60	8 Ohm to 100V transformer with different power taps: 60 - 30 - 15 - 6 watt	31,00	**37,20** BGN
	T20IP	8 Ohm to 100V transformer with different power taps: 20 - 10 - 5 - 2.5 watt, Waterproof	50,00	**60,00** BGN
	PAINTCAB-6	Optional painting of MASK6 or OVO5 cabinet speaker ranges in any RAL colour. Minimum order quantity of 12 pieces. Price is per piece.	54,00	**64,80** BGN
	PAINTCAB-8	Optional painting of MASK8 or OVO8 cabinet speaker ranges in any RAL colour. Minimum order quantity of 12 pieces. Price is per piece.	58,00	**69,60** BGN
	PAINTCM	Optional painting of 5", 6.5" and 8" CM, CMR and CMS ceiling speakers in any RAL colour. Minimum quantity is 12 pieces. Price is per piece.	50,00	**60,00** BGN
	PAINTCMM	Optional painting of 3" and 4" CM, CMR and CMS ceiling speakers in any RAL colour. Minimum quantity is 12 pieces. Price is per piece.	35,00	**42,00** BGN
	PAINTCOL	Optional painting of COL and COLW loudspeaker ranges in any RAL colour. Minimum quantity is 12 pieces. Price is per piece.	66,00	**79,20** BGN
	PAINTMP	Optional painting of MP and MPH soundprojector ranges in any RAL colour. Minimum quantity is 12 pieces. Price is per piece.	56,00	**67,20** BGN
	PAINTMPLT	Optional painting of MPLT30 and H30LT loudspeaker ranges in any RAL colour. Minimum quantity is 12 pieces. Price is per piece.	72,00	**86,40** BGN
	PAINTSPH	Optional paintinging of SPH loudspeakers in any RAL colour. Minimum quantity is 12 pieces. Price is per piece.	72,00	**86,40** BGN

	Model	Description	BGN Netto (ex. VAT)	BGN + 20% DDS (incl. VAT)
		VINCI AUDIOPHILE SERIES		
	VINCI 2125	Audiophile Integrated Amplifier, 4 digital, 3 analogue stereo inputs and 1 high class phono input Rated Outpit Power 2x80 Watts @ 8 Ohm, 2x125 Watts @ 4 Ohm; THD: <0.038%; S/N Ratio: >96dB Frequency Response: 10Hz-60kHz(+1/-3dB) Dimensions (WxHxD): 445x80x450mm; Weight: 11.6kg;	*751,00*	***901,20*** BGN
	new **VINCI4-BL** **VINCI4-W**	Reference Bookshelf Speaker; 4" paper woofer; 0.75" silk dome tweeter, Bass Reflex cabinet Dynamic Power: 120 Watts, Nominal impedance 6 Ohm; 84dB/1W/1m Frequency Response: 70Hz-25kHz, Cabinet material: High gloss finish MDF in black or white Dimensions (HxWxD): 210x136x164mm; Optional bracket VINCI5BRA	*70,00*	***84,00*** BGN
	VINCI5-BL **VINCI5-W**	Reference Bookshelf Speaker; 5.25" poly-cone woofer; 0.75" silk dome tweeter, Bass Reflex cabinet Recommended Amplifier Power: 30 to 160 Watts, no clipping; Nominal impedance 6 Ohm; Frequency Response: 60Hz-25kHz, Cabinet material: High gloss finish MDF in black or white Dimensions (HxWxD): 254x176x198mm; Weight: 3.5kg, Optional bracket VINCI5BRA	*111,00*	***133,20*** BGN
	VINCI5BRA-BL **VINCI5BRA-W**	Bracket for easy tilting and rotating of VINCI4 & VINCI5 speakers. Priced per piece, sold in pairs only.		
	new **VINCI7**	Reference Bookshelf Speaker; 7" poly-cone woofer; 1" silk dome tweeter, Bass Reflex cabinet Dynamic Power: 200 Watts, Nominal impedance 6 Ohm; 87dB/1W/1m Frequency Response: 50Hz-25kHz, Cabinet material: High gloss finish MDF, black Dimensions (HxWxD): 370x220x315mm; Weight: 10.1kg	*321,00*	***385,20*** BGN
	new **VINCI8S-BL** **VINCI8S-W**	Active compact 8" subwoofer, Dynamic power 125W, High gloss paint finish MDF cabinet, active crossover, line or speaker level stereo input, adjustable low-cut SPL: 89dB (1W/1m); Max SPL: 109dB; Frequency Response: 20-120Hz (adjustable); Dimensions (HxWxD): 345x262x405 mm; black or white	*325,00*	***390,00*** BGN

Tel: (02) 978 20 25 (office)
Fax: (02) 978 58 70
www.musicworld.bg

Please note all prices in the first column are without V.A.T.!!!

ProTechnica EOOD
Iskarsko Shaussee 7
BG-1528 Sofia